



Floor Standing Unit

INVERTER FVXS-F / RK(X)S-G



Wireless remote control as standard



The Daikin floor standing unit for home use has a contemporary design, is extremely quiet, energy-efficient and creates a very comfortable climate the whole year round. The unit can be installed against the wall or recessed.

- **Inverter technology:** reduces the power consumption by up to 30% compared to non inverter units and ensures maximum comfort, operating silence and reliability.
- **Wireless remote controller with weekly timer:** provides a 7-day schedule timer, enabling daily or weekly programming. Up to 4 actions per day possible.
- **Home Leave operation:** automatically keeps the room temperature at a specified comfort level during extended absence, by switching to heating when it reaches the minimum level and to cooling at the maximum level.
- **Night set mode:** prevents any sudden change in room temperature by gently raising/lowering the temperature before the system stops, so you can sleep more comfortably.
- **Powerful operation:** activates the maximum air volume for 20 minutes. After this, the system automatically returns to its original setting.
- **Titanium apatite photocatalytic air purifying filter:** superior adsorption power. Besides mould and odours, it also adsorbs and decomposes bacteria and viruses for effective purification and deodorisation of the air.
- **ECONO mode:** reduces power consumption so that other appliances that need large power supply can be used.
- **Dry programme:** reduces humidity in the rooms without variations in internal temperature.
- **Silent operation function:** increase comfort by further reducing the already 'whisper quiet' noise emissions.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.

Height	600mm
Width	700mm
Depth	210mm



FVXS25F

Height	550mm
Width	765mm
Depth	285mm



RXS25G

See tables overleaf for full list of dimensions

**ENERGY LABEL:
CLASS
A**

COOLING ONLY

INVERTER

Indoor Units				FVXS25F	FVXS35F	FVXS50F
Capacity	Cooling capacity	Minimum	kW	1.3	1.4	1.4
		Standard	kW	2.5	3.5	5.0
		Maximum	kW	3.0	3.8	5.6
EER	Nominal		4.39	3.43	3.23	
Annual energy consumption			kWh	285	510	775
Energy Label	cooling			A	A	A
Dimensions	(Height x Width x Depth)			mm	600x700x210	600x700x210
Weight				kg	14	14
Air Flow Rate	Cooling	H/M/L/SL	m³/min	8.2 / 6.5 / 4.8 / 4.1	8.5 / 6.7 / 4.9 / 4.A5	10.7 / 9.2 / 7.8 / 6.6
Sound Power	Cooling	High	dBA	54	55	56
Sound Pressure	Cooling	High	dBA	38 / 32 / 26 / 23	39 / 33 / 27 / 24	44 / 40 / 36 / 32
Refrigerant				Type	R-410A	
Power Supply					1~/220-240V/50Hz	
Controller					ARC452A1	
Outdoor Unit				RKS25G	RKS35G	RKS50G
Dimensions	(Height x Width x Depth)			mm	550x765x285	550x765x285
Weight				kg	34	48
Operation Range	Cooling	Min~Max	°CDB	-10~46	-10~46	-10~46
Sound Power	Cooling	High	dBA	61	63	62
Sound Pressure (Low)	Cooling	High	dBA	43	44	44
Sound Pressure (High)	Cooling	High	dBA	46	48	48
Refrigerant				Type	R-410A	
Power Supply					1~/220-240V/50Hz	
Piping connections	Liquid (OD)/Gas		mm	6.35 / 9.52		6.35 / 12.7
Piping Length (Maximum)				m	20	30
Max Installation Height Difference				m	15	20

HEAT PUMP

INVERTER

Indoor Units				FVXS25F	FVXS35F	FVXS50F
Capacity	Cooling capacity	Minimum	kW	1.3	1.4	1.4
		Standard	kW	2.5	3.5	5.0
		Maximum	kW	3.0	3.8	5.6
	Heating capacity	Minimum	kW	1.3	1.4	1.4
		Standard	kW	3.4	4.5	5.8
		Maximum	kW	4.5	5.0	8.1
EER / COP	Cooling / Heating		4.39 / 4.30	3.43 / 3.69	3.23 / 3.63	
Annual energy consumption			kWh	285	510	775
Energy Label	cooling / heating			A / A	A / A	A / A
Dimensions	(Height x Width x Depth)			mm	600x700x210	600x700x210
Weight				kg	14	14
Air Flow Rate	Cooling	H/M/L/SL	m³/min	8.2 / 6.5 / 4.8 / 4.1	8.5 / 6.7 / 4.9 / 4.5	10.7 / 9.2 / 7.8 / 6.6
	Heating	H/M/L/SL	m³/min	8.8 / 6.9 / 5.0 / 4.4	9.4 / 7.3 / 5.2 / 4.7	11.8 / 10.1 / 8.5 / 7.1
Sound Power	Cooling	High	dBA	54	55	56
	Heating	High	dBA	54	55	57
Sound Pressure	Cooling	H/M/L/SL	dBA	38 / 32 / 26 / 23	39 / 33 / 27 / 24	44 / 40 / 36 / 32
	Heating	H/M/L/SL	dBA	38 / 32 / 26 / 23	39 / 33 / 27 / 24	45 / 40 / 36 / 32
Refrigerant				Type	R-410A	
Power Supply					1~/220-240V/50Hz	
Controller					ARC452A1	
Outdoor Unit				RXS25G	RXS35G	RXS50G
Dimensions	(Height x Width x Depth)			mm	550x765x285	550x765x285
Weight				kg	34	48
Operation Range	Cooling	Min~Max	°CDB	-10~46	-10~46	-10~46
	Heating	Min~Max	°CWB	-15~20	-15~20	-15~18
Sound Power	Cooling	High	dBA	61	63	62
Sound Pressure (Low)	Cooling	High	dBA	43	44	44
	Heating	High	dBA	44	45	45
Sound Pressure (High)	Cooling	High	dBA	46	48	48
	Heating	High	dBA	47	48	48
Refrigerant				Type	R-410A	
Power Supply					1~/220-240V/50Hz	
Piping connections	Liquid (OD)/Gas		mm	6.35/9.52/18		6.35/12.7/18
Piping Length (Maximum)				m	20	30
Max Installation Height Difference				m	15	20

www.daikin.co.uk

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

Daikin products are distributed by:

FSC



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.